



Specification

System	Processor	Intel® Core i3-6100U Dual-core, clock speed 2.30G, TDP 15W
	Chipset	CPU Integrated
	System Memory	1x DDR3L 1333/1600MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	GPIO	8x programmable GPIO (Optional)
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	10.1" (16:10 ratio)
	Brightness	350 nits
	Resolution	1280 x 800 (HD)
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB	2x USB3.0, 2x USB2.0
	Serial Port	2x RS-232
	LAN	2x LAN
	Display	1x VGA, 1x HDMI
Audio	Internal Speaker	Speaker Header x1
Power	Power Supply	84W Power Adapter
	Connector	DCIN Input : 9V~28V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP65, Aluminum front bezel, true flat design
	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-25°C ~ 75°C
	Humidity	5% ~ 95% RH non-condensing
Dimensions (WxDxH)		257.2 x 170.9 x 51 mm
Weight		2.0 kg
Mounting		VESA Mount 75 x 75 mm
OS Supported		Win7, Win 8, Win10 IOT, Linux

SIDE



FRONT



BACK

