



Specification

System	Processor	Intel® Core i5-7200U Dual-core, clock speed 2.50G, TDP 15W
	Chipset	CPU Integrated, TPM 2.0 support
	System Memory	1x DDR3L 1333/1600MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	DIO	Digital I/O 4 in/ 4 out
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	43"
	Brightness	400 nits
	Resolution	1920 x 1080 (FHD)
	Touch Screen	True-Flat PCAP Touch (2 Points, 10 Points, 30 Points)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB	2x USB 3.0, 4x USB 2.0
	Serial Port	2x RS-232 (Optional 4x RS-232 or 3x RS-232 + 1x RS-485)
	LAN	2x LAN
	Display	1x VGA, 1xHDMI
Audio	Internal Speaker	Stereo speaker (5Wx 2) (Optional)
Power	Power Supply	120W Power Adapter (Input 90~264 VAC , Output: 24 VDC, 5A)
	Connector	DCIN Input : 9V~28V Connector types:1x PHOENIX Connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP67, Stainless steel front bezel, true flat design
	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-25°C ~ 75°C
	Humidity	5% ~ 95% RH non-condensing

Dimensions (WxDxH)	1084 x 677 x 89.2 mm
Weight	37 kg
Mounting	VESA Mount 400 x 600 mm
OS Supported	Win7, Win 8, Win 10 Pro, Win10 IOT, Linux

