



Specification

LCD Touch Panel

LCD Size	19" (5:4 ratio)
Brightness	250 nits or 1000 nits (Optional)
Resolution	1280 x 1024
Colors	16.7M
Active Area	376.32 (H) x 301.06 (V) (mm)
Pixel Pitch	0.294 x 0.294 (mm)
Viewing Angle	85/85 (H), 80/80 (V)
Contrast Ratio	1000 : 1
LED Life Time	30,000 Hrs
Touch Screen	True-Flat PCAP Touch (10 Points)
Surface Hardness	7H
Surface type	Non-reflective surface

External I/O Ports

Display Input	VGA + DP + HDMI
Display Control	OSD

Audio

Internal Speaker	2 x 5 Watts, internal stereo speaker (Optional)
------------------	---

Power

Power Supply	DC IN 12V or Universal 90-240V, 12V/50W Power adapter
--------------	---

Environment

Ventilation	Fanless
Dust & Water Proof	Front IP67, Aluminum front bezel, True-Flat design
Operating Temperature	0°C ~ 60°C (32~140°F)
Storage Temperature	-20°C ~ 70°C (-4~176°F)
Humidity	10% ~ 95% R/H non-condensing

Dimensions (WxDxH)

424.72 x 349.5 x 50 mm, suggested cut out size 408.7 x 334.5 mm

Weight

3.2 kg

Mounting

VESA Mount 75 x 75 mm and 100 x 100 mm, or Panel Mount with Panel Mount bracket (Optional)

