



Ultra Slim Aluminum front bezel
True-flat design 21.5" Panel PC



Specification

System	Processor Chipset System Memory Storage Device Graphic Engine DIO Watchdog	Intel Celeron J3455 CPU Quad-Core, up to 2.3 GHz, TDP 10W CPU Integrated DDR3L-1333/1600/1866 MHz, 1 x SO-DIMM, up to 8GB 1 x SATA 3.0 header, 1 x M.2 Key-B Slot Intel HD Graphics 1 x GPIO Header (Programmable support 8-bit GPIO) With Watchdog Timer
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	21.5" 250 nits (400/1000 nits optional) 1920 x 1080 True-Flat PCAP Touch (IP67 Front)
Expansion	M.2 Slot	1 x M.2 Key-B slot (5G/4G with 1 x SIM card header) 1 x M.2 Key-E slot (WIFI + BT)
External I/O Ports	USB Serial Port LAN Display	2x USB 3.0, 2x USB 2.0 (Optional 2x USB 3.0, 4x USB 2.0) 2x RS-232 (Optional 4x RS-232 or 3x RS-232 + 1x RS-485) 2x LAN 1x HDMI, 1x VGA
Audio	Internal Speaker	2x Stereo speaker (Optional)
Power	Power Supply Connector	Power adapter DCIN Input: 12V, Connector type: 1x Phoenix connector
Environment	Ventilation Dust & Water Proof Operating Temperature Storage Temperature Humidity	Fanless Front IP67 0 ~ 60°C (32 ~ 140°F) -20 ~ 70°C (-4 ~ 176°F) 5% ~ 95% R/H, non-condensing

Dimensions (WxDxH) 537.8 x 329.3 x 50 mm, suggested cut out size is 514.4 x 305.9 mm

Weight 5 kg

Mounting VESA Mount 100 x 100 mm, Panel mount kit (Optional)

OS Supported Win7, Win 8, Win10 IOT, Linux

