



Specification

LCD Touch Panel

LCD Size	21.5" (16:9 ratio)
Brightness	250 nits or 1000 nits (Optional)
Resolution	1920x 1080
Colors	16.7M
Active Area	476.64 (H) x 268.11 (V) (mm)
Pixel Pitch	248.25 x 248.25 (um)
Viewing Angle	89/89 (H), 89/89 (V)
Contrast Ratio	3000 : 1
LED Life Time	50,000 Hrs
Touch Screen	True-Flat PCAP (10 Points) or with AG coating (Optional)
Surface Hardness	7H
Surface type	Non-reflective surface

External I/O Ports

Display Input	VGA+DP+HDMI
Display Control	OSD

Audio

Internal Speaker	2 x 5 Watts, stereo speaker (internal)
------------------	--

Power

Power Supply	DC IN 12V or Universal 90-240V, 12V/50W Power adapter
--------------	---

Environment

Ventilation	Fanless
Dust & Water Proof	Front IP67, Aluminum front bezel, true flat PCAP touch design
Operating Temperature	0°C ~ 60°C (32~140°F)
Storage Temperature	-20°C ~ 70°C (-4~176°F)
Humidity	10% ~ 95% R/H non-condensing

Dimensions (WxDxH)

537.8 x 329.3 x 50 mm

Weight

5.4 kg

Mounting

VESA Mount 75 x 75 mm and 100 x 100 mm or Panel Mount with Panel Mount bracket

