



### Specification

<b>LCD Touch Panel</b>	LCD Size	10.1" (16 : 10 ratio)
	Brightness	350 nits or 1000 nits sunlight readable (Optional)
	Resolution	1280 x 800 (HD)
	Colors:	16.7M
	Active Area	216.96 x 135.6 (mm)
	Pixel Pitch	0.1695 x 0.1695 (mm)
	Viewing Angle	85/85 (H) , 85/85 (V)
	Contrast Ratio	800 : 1
	LED Life Time	25,000 Hrs
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
	Optical Bonding	Support (Optional)
<b>External I/O Ports</b>	Display Input	VGA + DP + HDMI or VGA + DVI
	Display Control	OSD Key
	Ambient Light Sensor	Support (Optional)
<b>Audio</b>	Internal Speaker	Speaker Header x 1
<b>Power</b>	Power Supply Connector	DC 12V or Universal 90-240V, 12V/50W Power adapter (Optional)
<b>Environment</b>	Ventilation	Fanless
	Dust & Water Proof	IP67 Front, Aluminum front bezel, true-flat PCAP touch design
	Operating Temperature	-20°C ~ 70°C
	Storage Temperature	-30°C ~ 80°C
	Humidity	5% ~ 95% RH non-condensing
<b>Dimensions (WxDxH)</b>		257.2 x 170.9 x 32 mm
<b>Weight</b>		1.8 kg
<b>Mounting</b>		VESA Mount 75 x 75 mm

