



Specification

System	Processor Chipset System Memory Storage Device Graphic Engine DIO Watchdog	Intel Celeron Apollo Lake N3350 Dual core 6W processor CPU Integrated, TPM 2.0 support 1x DDR3L 1600/1866MHz SO-DIMM up to 8GB 1x 2.5" SATA HDD or SSD or mSATA module Intel HD Graphics Digital I/O 8 in/ 8 out With Watchdog Timer
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	10.1" (16:10 ratio) 1000 nits 1280 x 800 (HD) True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB Serial Port LAN Display DIO	2x USB3.0, 2x USB2.0 2x RS-232/RS-422/RS-485 2x LAN 1x VGA, 1xHDMI 2x Phoenix connectors with DIO 8 in/ 8 out (Located at left hand side of housing)
Audio	Internal Speaker	Speaker Header x1
Power	Power Supply Connector	84W Power Adapter DCIN Input : 9V~36V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation Dust & Water Proof Operating Temperature Storage Temperature Humidity	Fanless Front IP65 ,Aluminum front bezel, true flat design 0°C ~ 60°C -25°C ~ 75°C 5% ~ 95% RH non-condensing
Dimensions (WxDxH)	257.2 x 170.9 x 51 mm	
Weight	2.0 kg	
Mounting	VESA Mount 75 x 75 mm	
OS Supported	Win7, Win 8 , Win10 IOT, Linux	

SIDE



FRONT



BACK

