



Specification

System	Processor	Intel Celeron Apollo Lake N3350 Dual core 6W processor
	Chipset	CPU Integrated, TPM 2.0 support
	System Memory	1x DDR3L 1600/1866MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	DIO	Digital I/O 8 in/ 8 out
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	10.1" (16:10 ratio)
	Brightness	350 nits
	Resolution	1280 x 800 (HD)
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB	2x USB3.0, 2x USB2.0
	Serial Port	2x RS-232/RS-422/RS-485
	LAN	2x LAN (1x POE-PD Optional)
	Display	1x VGA, 1xHDMI
Audio	Internal Speaker	Speaker Header x1
Power	Power Supply	84W Power Adapter
	Connector	DCIN Input : 9V~36V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP65 ,Aluminum front bezel, true flat deign
	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-25°C ~ 75°C
	Humidity	5% ~ 95% RH non-condensing
Dimensions (WxDxH)	257.2 x 170.9 x 51 mm	
Weight	2.0 kg	
Mounting	VESA Mount 75 x 75 mm	
OS Supported	Win7, Win 8, Win10 IOT, Linux	

SIDE



FRONT



BACK

